



SUPER DUCT



**SUPER DUCT
HEAVY DUTY
"ALL WEATHER"**



SUPER METAL



40 micron

code								€
Duct TAPE ECO (ST 101)								
ST 4471101	vrac	8714828010067	●	48 x 50	302 gr	1620	36	6,08
Super Duct (ST 401)								
ST 4471960	vrac	8714828000754	●	50 x 50	492 gr	960	24	8,05
ST 4471890	vrac	8714828000778	●	50 x 50	506 gr	960	24	8,05
ST 4471900	vrac	8714828000761	●	50 x 50	498 gr	960	24	8,05
Super Duct Heavy Duty (ST 501)								
ST 4474241	vrac	8714828001362	●	50 x 50	650 gr	1080	24	11,37
Super Metal - 40 micron								
ST 9105050	vrac	5420000025158	alu - 40 micron	50 x 50	453 gr	1080	24	4,74
ST 9107075	vrac	5420000025165	alu - 40 micron	75 x 50	759 gr	1080	16	7,10
ST 9108120	vrac	5420000025172	alu - 40 micron	100 x 50	986 gr	1080	12	10,23

	SUPER DUCT ECO	SUPER DUCT	SUPER DUCT HEAVY DUTY	SUPER METAL
Temperatuursbestendigheid Résistance thermique	-10°C → 75°C	-15°C → 60°C	-25°C → 80°C	-20°C → 120°C
Kleefkracht Adhésivité	sterk <i>forte</i>	zeer sterk <i>très forte</i>	zeer sterk <i>très forte</i>	goed <i>bonne</i>
Drager Support	Polyester weefsel <i>Fibre polyester</i>	Polyester weefsel <i>Fibre polyester</i>	PE vezelbekleding <i>couvert fibre PE</i>	ALU
Kleeflaag Adhésif	synthetisch rubber <i>caoutchouc synth.</i>	Hotmelt	synthetisch rubber <i>caoutchouc synth.</i>	acrylaat <i>acrylique</i>
Rekbaarheid Elasticité	-	-	-	-